



AdBlue® by OCI

Urea Solution 32,5%

OCI NITROGEN B.V.
Poststraat 1, 6135 KR Sittard
P.O. Box 601, 6160 AP Geleen
The Netherlands
T +31 46 7020203
info.agro@ocinitrogen.com

Revision Date: 2025-05-22 (R6)

Property	Unit	Limits		Test Methods	
		min.	max.		
Urea content	% (mass fraction)	31,8	33,2	ISO 22241-2:2019, Annex B ISO 22241-2:2019, Annex C	
Refractive index (nD20)		1,3814	1,3843	ISO 22241-2:2019, Annex C	
Alkalinity as NH ₃	% (mass fraction)		0,2	ISO 22241-2:2019, Annex D	
Biuret	% (mass fraction)		0,3	ISO 22241-2:2019, Annex E	
Aldehydes	mg/kg		5	ISO 22241-2:2019, Annex F	
Insoluble matter	mg/kg		20	ISO 22241-2:2019, Annex G	
Phosphate (PO ₄)	mg/kg		0,5	ISO 22241-2:2019, Annex H ISO 22241-2:2019, Annex I	
Aluminium	mg/kg		0,5	ISO 22241-2:2019, Annex I	
Calcium	mg/kg		0,5		
Chromium	mg/kg		0,2		
Copper	mg/kg		0,2		
Iron	mg/kg		0,5		
Potassium	mg/kg		0,5		
Magnesium	mg/kg		0,5		
Sodium	mg/kg		0,5		
Nickel	mg/kg		0,2		
Zinc	mg/kg		0,2		
Product Carbon Footprint (PCF) ¹		Cradle to Gate		0,48 ton CO ₂ eq / ton AdBlue	
		Cradle to Grave		0,72 ton CO ₂ eq / ton AdBlue	
Storage Temperature °C	Minimum Shelf Life (month)	Freezing point	Boiling Point of Solution	Typical Characteristics	
≤ 10	36	-11°C to -15°C (12,2°F to 5°F)	Decomposition at: 100°C	Physical State	Liquid
≤ 25	18			Colour	Colourless / White
≤ 30	12			Odour	Ammonia (slight)

REMARKS

All data, suggestions and information given herein is deemed to be accurate and reliable, but is presented without warranty (expressed or implied) whatsoever. OCI Nitrogen B.V. does not accept any liability in connection with this information or use. It is the responsibility of each user to determine whether the information in this document is appropriate/suitable for their particular use, application or processing. Nothing in this document shall be deemed to alter or waive any provision of OCI Nitrogen's General Conditions of Sale or this disclaimer.

¹ Product Carbon Footprint is calculated on a cradle to gate basis (year 2023/2024 activity data) according to ISO 14067 and has been reviewed by an external panel of experts following requirements of ISO 14044. Cradle to Grave is calculated as Cradle to OCI gate + End of Life emission assuming the embedded carbon of 0.238 tonCO₂eq/ton AdBlue is converted into CO₂. More information is available upon request.